

Specifications:
Current rating:1.0A AC/DC
Voltage rating:250V AC/DC $\triangle A$
Contact resistance:20m ohm max.
Withstanding Voltage:500V AC/minute
Insulation resistance:1000M ohm min.
Temperature Rating:−40°C ~ +105°C

Materials:
Insulator:PBT (UL94V−0)
Contact :Copper Alloy
Finish:Selective Gold Plated

How To Order
4401−XXSR−XX−XX $\triangle A$
Blank:Black(Standard Color)
GR;Gray;BU:Blue
Blank Selective Gold Plated
08:Selective Gold Plated 8u”
15:Selective Gold Plated 15u”
30:Selective Gold Plated 30u”
SR:With Strain Relief
No. of Contacts

Dimension Information: $\triangle D$

Circuits	Dim.A	Dim.B	Circuits	Dim.A	Dim.B
6	12.30	5.08	30	42.78	35.56
8	14.84	7.62	34	47.86	40.64
10	17.38	10.16	36	50.40	43.18
12	19.92	12.70	40	55.48	48.26
14	22.46	15.24	44	60.56	53.34
16	25.00	17.78	50	68.18	60.96
18	27.54	20.32	56	75.80	68.58
20	30.08	22.86	60	80.88	73.66
24	35.16	27.94	64	85.96	78.74
26	37.70	30.48			

RoHS Compliant

H	14-Jul-2022	Add Plated Option	Lucy	DRAWN: Leo	GENERAL TOLERANCE: .X=±0.2 .XX=±0.15	 Neltron Industrial Co., Ltd.	DESCRIPTION: 2.54MM Flat Cable IDC Socket With Strain Relief	SIZE A4	D
G	18-Dec-2019	modify tolerance	Jamie						
F	30-Oct-2013	ECN-CN1310004	Andrew	CHECKED: Jeremy Liu	UNIT: mm				
E	04-Dec-2008	ECN-CN081211	zhangxh		SCALE: 1:1				
D	11-Sep-2008	ECN-CN080916	Leo	APPROVAL: MIKE WU	SHEET: 1 / 1				
A	10-MAR-2008	(P0001) (P0001)	Leo		PART NO: 4401-XXSR-XX-XX 				
REV	DATE	FILE	BY	PROJECTION:  					