
NPN Epitaxial Silicon Transistor

KSP42, KSP43



STRAIGHT LEAD
BULK PACK

TO−92−3
CASE 135AN

BENT LEAD
TAPE & REEL
AMMO PACK

TO−92 LF
CASE 135AR

Features

- Collector−Emitter Voltage:
  - KSP42: V_{CEO} = 300 V
  - KSP43: V_{CEO} = 200 V
- Collector Dissipation: P_C (max.) = 625 mW
- These Devices are Pb−Free, Halogen Free/BFR Free and are RoHS Compliant


ABSOLUTE MAXIMUM RATINGS

Values are at T_A = 25°C unless otherwise noted.

Symbol	Parameter		Value	Unit
V_{CBO}	Collector−Base Voltage	KSP42	300	V
		KSP43	200	
V_{CEO}	Collector−Emitter Voltage	KSP42	300	V
		KSP43	200	
V_{EBO}	Emitter−Base Voltage		6	V
I_C	Collector Current		500	mA
P_C	Collector Power Dissipation		625	mW
T_J	Junction Temperature		150	°C
T_{STG}	Storage Temperature		−55 to 150	°C

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.

MARKING DIAGRAM



A = Assembly Code
KSP4x = Device Code (x = 2 or 3)
Y = Year
WW = Work Week

ORDERING INFORMATION

See detailed ordering and shipping information on page 2 of this data sheet.

NOTE: Some of the devices on this data sheet have been **DISCONTINUED**. Please refer to the table on page 2.

© Semiconductor Components Industries, LLC, 2002

ORDERING INFORMATION

Part Number	Top Mark	Package	Shipping
KSP42BU	KSP42	TO−92−3 (Pb−Free), case 135AN	10,000 units / Bulk Bag
KSP42TA	KSP42	TO−92−3 (Pb−Free), case 135AR	2,000 units / Fan−Fold
KSP43TA	KSP43	TO−92−3 (Pb−Free), case 135AR	2,000 units / Fan−Fold

DISCONTINUED (Note 1)

KSP43BU	KSP43	TO−92−3 (Pb−Free), case 135AN	10,000 units / Bulk Bag

1. **DISCONTINUED:** This device is not recommended for new design. Please contact your **onsemi** representative for information. The most current information on this device may be available on www.onsemi.com.

ELECTRICAL CHARACTERISTICS

(Values are at T_A = 25°C unless otherwise noted.)

Symbol	Parameter		Conditions	Min	Max	Unit
BV_{CBO}	Collector−Base Breakdown Voltage	KSP42	I_C = 100 μA, I_E = 0	300		V
		KSP43		200		
BV_{CEO}	Collector−Emitter Breakdown Voltage (Note 2)	KSP42	I_C = 1 mA, I_B = 0	300		V
		KSP43		200		
BV_{EBO}	Emitter−Base Breakdown Voltage		I_E = 100 μA, I_C = 0	6		V
I_{CBO}	Collector Cut−Off Current	KSP42	V_{CB} = 200 V, I_E = 0		100	nA
		KSP43	V_{CB} = 160 V, I_E = 0		100	
I_{EBO}	Emitter Cut−Off Current	KSP42	V_{EB} = 6 V, I_C = 0		100	nA
		KSP43	V_{EB} = 4 V, I_C = 0		100	
h_{FE}	DC Current Gain (Note 2)		V_{CE} = 10 V, I_C = 1 mA	25		
			V_{CE} = 10 V, I_C = 10 mA	40		
			V_{CE} = 10 V, I_C = 30 mA	40		
V_{CE}(sat)	Collector−Emitter Saturation Voltage (Note 2)		I_C = 20 mA, I_B = 2 mA		0.5	V
V_{BE}(sat)	Base−Emitter Saturation Voltage (Note 2)		I_C = 20 mA, I_B = 2 mA		0.9	V
C_{ob}	Output Capacitance	KSP42	V_{CB} = 20 V, I_E = 0, f = 1 MHz		3	pF
		KSP43			4	
f_T	Current Gain Bandwidth Product		V_{CE} = 20 V, I_C = 10 mA, f = 100 MHz	50		MHz

Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.

2. Pulse test: pulse width ≤ 300 μs, duty cycle ≤ 2%.

Share Feedback
Your Opinion Matters

TYPICAL PERFORMANCE CHARACTERISTICS




Figure 1. DC Current Gain




Figure 2. Collector−Emitter Saturation Voltage and Base−Emitter Saturation Voltage




Figure 3. Current Gain Bandwidth Product





Figure 4. Current Gain Bandwidth Product

Share Feedback
Your Opinion Matters

TO−92 3 4.825x4.76
CASE 135AN
ISSUE O

DATE 31 JUL 2016



NOTES: UNLESS OTHERWISE SPECIFIED


A) DRAWING WITH REFERENCE TO JEDEC TO−92 RECOMMENDATIONS.
B) ALL DIMENSIONS ARE IN MILLIMETERS.
C) DRAWING CONFORMS TO ASME Y14.5M−2009.


DOCUMENT NUMBER:	**98AON13880G**	Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red.	
DESCRIPTION:	**TO−92 3 4.825X4.76**		**PAGE 1 OF 1**

onsemi and onsemi are trademarks of Semiconductor Components Industries, LLC dba **onsemi** or its subsidiaries in the United States and/or other countries. **onsemi** reserves the right to make changes without further notice to any products herein. **onsemi** makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. **onsemi** does not convey any license under its patent rights nor the rights of others.

TO−92 3 4.83x4.76 LEADFORMED
CASE 135AR
ISSUE O

DATE 30 SEP 2016





NOTES: UNLESS OTHERWISE SPECIFIED

A) DRAWING WITH REFERENCE TO JEDEC TO-92 RECOMMENDATIONS.
B) ALL DIMENSIONS ARE IN MILLIMETERS.
C) DRAWING CONFORMS TO ASME Y14.5M-1994

DOCUMENT NUMBER:	**98AON13879G**	Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red.	
DESCRIPTION:	**TO−92 3 4.83X4.76 LEADFORMED**		**PAGE 1 OF 1**

onsemi and onsemi are trademarks of Semiconductor Components Industries, LLC dba **onsemi** or its subsidiaries in the United States and/or other countries. **onsemi** reserves the right to make changes without further notice to any products herein. **onsemi** makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. **onsemi** does not convey any license under its patent rights nor the rights of others.

onsemi, , and other names, marks, and brands are registered and/or common law trademarks of Semiconductor Components Industries, LLC dba "**onsemi**" or its affiliates and/or subsidiaries in the United States and/or other countries. **onsemi** owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of **onsemi**'s product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent−Marking.pdf. **onsemi** reserves the right to make changes at any time to any products or information herein, without notice. The information herein is provided "as−is" and **onsemi** makes no warranty, representation or guarantee regarding the accuracy of the information, product features, availability, functionality, or suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using **onsemi** products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by **onsemi**. "Typical" parameters which may be provided in **onsemi** data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. **onsemi** does not convey any license under any of its intellectual property rights nor the rights of others. **onsemi** products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use **onsemi** products for any such unintended or unauthorized application, Buyer shall indemnify and hold **onsemi** and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that **onsemi** was negligent regarding the design or manufacture of the part. **onsemi** is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

ADDITIONAL INFORMATION

TECHNICAL PUBLICATIONS:
Technical Library: www.onsemi.com/design/resources/technical−documentation
onsemi Website: www.onsemi.com

ONLINE SUPPORT: www.onsemi.com/support
For additional information, please contact your local Sales Representative at www.onsemi.com/support/sales